



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 06/05/2018

Reviewed on 06/05/2018

* 1 Identification

- **Product identifier**
- **Trade name: DECK-SIL® EP-1700 Seal Component B**
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Product description** Penetrating epoxy healer sealer
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Advanced Chemical Technologies, Inc.
9608 North Robinson Avenue
Oklahoma City, OK 73114
Phone: 405-843-2585
Fax: 405-843-2596
Web: www.advchemtech.com
Emergency telephone number:
Chemtel: 1-800-255-3924

DECK-SIL® Product for use under U.S. Patent No. 9,242,269.

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS09 Environment

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Skin Sens. 1 H317 May cause an allergic skin reaction.

(Contd. on page 2)



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 06/05/2018

Reviewed on 06/05/2018

• **Label elements**

• **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

• **Hazard pictograms**



GHS02 GHS05 GHS07 GHS08 GHS09

• **Signal word** Danger

• **Hazard-determining components of labeling:**

4-nonylphenol, branched
cyclohex-1,2-ylenediamine
Benzyl alcohol
2,4,6-tris(dimethylaminomethyl)phenol

• **Hazard statements**

Flammable liquid and vapor.
Harmful if swallowed.
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
Suspected of damaging fertility or the unborn child.
Very toxic to aquatic life.
Very toxic to aquatic life with long lasting effects.

• **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Use explosion-proof electrical/ventilating/lighting/equipment.
Do not breathe dusts or mists.
Wear protective gloves / eye protection / face protection.
Wear protective gloves.
Wear eye protection / face protection.
Ground/bond container and receiving equipment.
Keep container tightly closed.
Use only non-sparking tools.
Avoid release to the environment.
Take precautionary measures against static discharge.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Contaminated work clothing must not be allowed out of the workplace.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Immediately call a poison center/doctor.
If swallowed: Call a poison center/doctor if you feel unwell.
Specific treatment (see on this label).
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Wash contaminated clothing before reuse.
IF exposed or concerned: Get medical advice/attention.
If skin irritation or rash occurs: Get medical advice/attention.
If swallowed: Rinse mouth. Do NOT induce vomiting.

(Contd. on page 3)



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 06/05/2018

Reviewed on 06/05/2018

In case of fire: Use for extinction: CO₂, powder or water spray.

Collect spillage.

Store locked up.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

• **Unknown acute toxicity:**

65 percent of the mixture consists of ingredient(s) of unknown toxicity.

• **Classification system:**

• **NFPA ratings (scale 0 - 4)**



• **HMS-ratings (scale 0 - 4)**



• **Other hazards** None known

3 Composition/information on ingredients

• **Chemical characterization: Mixtures**

• **Description:** Mixture of substances listed below with nonhazardous additions.

• **Dangerous Components:**

CAS: 84852-15-3	4-nonylphenol, branched ⚠ Repr. 2, H361; ⚠ Skin Corr. 1B, H314; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Acute Tox. 4, H302	25-50%
CAS: 1330-20-7 RTECS: ZE 2100000	xylene ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	15-35%
CAS: 694-83-7	cyclohex-1,2-ylenediamine ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318; ⚠ Skin Sens. 1, H317; H227	5-10%
CAS: 90-72-2	2,4,6-tris(dimethylaminomethyl)phenol ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2A, H319	5-10%
CAS: 100-51-6 RTECS: DN 3150000	Benzyl alcohol ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332	5-10%

4 First-aid measures

• **Description of first aid measures**

• **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• **After inhalation:**

In case of unconsciousness, place patient securely on side position for transportation.

Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist.

• **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

(Contd. on page 4)



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 06/05/2018

Reviewed on 06/05/2018

- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:**
Drink copious amounts of water and provide fresh air. Immediately call a doctor.
Do not induce vomiting.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:**
Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Ensure adequate ventilation.
Use neutralizing agent.
Absorb with liquid-binding material (ie. sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Open and handle receptacle with care.
Ensure good ventilation/exhaustion at the workplace.
Avoid contact with skin, eyes and clothing
Avoid breathing fume/gas/mist/vapors/spray.
Do not take internally.
Use personal protection equipment as outlined in section 8.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect from heat.
Protect against electrostatic charges.
Keep protective respiratory device available.

(Contd. on page 5)



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 06/05/2018

Reviewed on 06/05/2018

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a well ventilated place.
Store in a cool, dry place away from sparks and flame.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Protect from heat and direct sunlight.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**

- **Components with occupational exposure limits:**

1330-20-7 xylene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI

100-51-6 Benzyl alcohol

WEEL	Long-term value: 10 ppm
------	-------------------------

- **Ingredients with biological limit values:**

1330-20-7 xylene

BEI	1.5 g/g creatinine urine end of shift Methylhippuric acids
-----	---

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing Date 06/05/2018

Reviewed on 06/05/2018

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Penetration time of glove material**

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

- **Eye protection:** Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Liquid
Color: Dark amber

- **Odor:** Solvent-like
- **Odor threshold:** Not determined.

- **pH-value @ 20 °C (68 °F):** 12

- **Change in condition**

Melting point/Melting range: Not determined.
Boiling point/Boiling range: 137 °C (279 °F)

- **Flash point:** 30 °C (86 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** 435 °C (815 °F)

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- **Explosion limits:**

Lower: 1.1 Vol %
Upper: 13.0 Vol %

- **Vapor pressure @ 20 °C (68 °F):** 6.7 hPa (5 mm Hg)

- **Density @ 20 °C (68 °F):** 0.9 g/cm³ (7.511 lbs/gal)

- **Relative density** Not determined.

- **Vapour density** Not determined.

- **Evaporation rate** Not determined.

- **Solubility in / Miscibility with**

Water: Fully miscible.

- **Partition coefficient (n-octanol/water):** Not determined.

- **Viscosity:**

Dynamic: Not determined.
Kinematic: Not determined.

- **Solvent content:**

Organic solvents: 35.0 %

VOC content: 35.0 %

- **Other information** No further relevant information available.

(Contd. on page 7)



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 06/05/2018

Reviewed on 06/05/2018

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:**
Strong oxidizing agents.
Strong acids, strong bases
- **Hazardous decomposition products:** Carbon dioxide, carbon monoxide and nitrogen oxides.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

1330-20-7 xylene

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:**
Strong caustic effect on skin and mucous membranes.
May cause an allergic skin reaction.
- **on the eye:**
Strong irritant with the danger of severe eye injury.
Corrosive effect.
Causes serious eye irritation.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Corrosive
Irritant
Swallowing will lead to a corrosive effect on mouth and throat and to the danger of perforation of esophagus and stomach.
- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
-----------	--------	---

- **NTP (National Toxicology Program)**

None of the ingredients are listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients are listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:**
Avoid release into the environment. Runoff from fire control or dilution water may cause pollution.

(Contd. on page 8)



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 06/05/2018

Reviewed on 06/05/2018

- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Very toxic for fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Must not reach bodies of water or drainage ditch undiluted or unneutralized.
Danger to drinking water if even extremely small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Very toxic for aquatic organisms
Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Do not allow product to reach sewage system.
It is the generators responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state and federal environmental regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA**
- **UN proper shipping name**
- **DOT**
- **ADR**
- **IMDG**
- **IATA**
- **Transport hazard class(es)**
- **DOT**

UN2920

Corrosive liquids, flammable, n.o.s.

UN2920 Corrosive liquids, flammable, n.o.s. (4-nonylphenol, branched, Xylenes), ENVIRONMENTALLY HAZARDOUS

CORROSIVE LIQUID, FLAMMABLE, N.O.S. (4-nonylphenol, branched, XYLENES), MARINE POLLUTANT

CORROSIVE LIQUID, FLAMMABLE, N.O.S.



- **Class** 8 Corrosive substances

(Contd. on page 9)



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 06/05/2018

Reviewed on 06/05/2018

· **Label** 8, 3

· **ADR**



· **Class** 8 (CF1) Corrosive substances
· **Label** 8+3

· **IMDG**



· **Class** 8 Corrosive substances
· **Label** 8/3

· **IATA**



· **Class** 8 Corrosive substances
· **Label** 8 (3)
· **Packing group** II
· **DOT, ADR, IMDG, IATA** II
· **Environmental hazards:** Product contains environmentally hazardous substances: 4-nonylphenol, branched
· **Marine pollutant:** Yes
· **Special marking (ADR):** Symbol (fish and tree)
· **Special precautions for user** Symbol (fish and tree)
· **Danger code (Kemler):** Warning: Corrosive substances
· **EMS Number:** 83
· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** F-E,S-C
· **Transport/Additional information:** Not applicable.
· **DOT**
· **Quantity limitations** On passenger aircraft/rail: 1 L
On cargo aircraft only: 30 L
· **Remarks:** Special marking with the symbol (fish and tree).

· **ADR**

· **Excepted quantities (EQ)** Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

· **IMDG**

· **Limited quantities (LQ)** 1L



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 06/05/2018

Reviewed on 06/05/2018

• **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

• **UN "Model Regulation":**

UN2920, Corrosive liquids, flammable, n.o.s. (4-nonylphenol, branched, Xylenes), ENVIRONMENTALLY HAZARDOUS, 8 (3), II

15 Regulatory information

• **Safety, health and environmental regulations/legislation specific for the substance or mixture**

• **Sara**

• **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

• **Section 313 (Specific toxic chemical listings):**

1330-20-7 xylene

• **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

• **Proposition 65**

• **Chemicals known to cause cancer:**

None of the ingredients are listed.

• **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

• **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

• **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

• **Carcinogenic categories**

• **EPA (Environmental Protection Agency)**

1330-20-7 xylene

I

• **TLV (Threshold Limit Value established by ACGIH)**

1330-20-7 xylene

A4

• **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients are listed.

• **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

• **Hazard pictograms**



GHS02 GHS05 GHS07 GHS08 GHS09

• **Signal word** Danger

• **Hazard-determining components of labeling:**

4-nonylphenol, branched
cyclohex-1,2-ylenediamine



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 06/05/2018

Reviewed on 06/05/2018

Benzyl alcohol
2,4,6-tris(dimethylaminomethyl)phenol

• **Hazard statements**

Flammable liquid and vapor.
Harmful if swallowed.
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
Suspected of damaging fertility or the unborn child.
Very toxic to aquatic life.
Very toxic to aquatic life with long lasting effects.

• **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Use explosion-proof electrical/ventilating/lighting/equipment.
Do not breathe dusts or mists.
Wear protective gloves / eye protection / face protection.
Wear protective gloves.
Wear eye protection / face protection.
Ground/bond container and receiving equipment.
Keep container tightly closed.
Use only non-sparking tools.
Avoid release to the environment.
Take precautionary measures against static discharge.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Contaminated work clothing must not be allowed out of the workplace.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Immediately call a poison center/doctor.
If swallowed: Call a poison center/doctor if you feel unwell.
Specific treatment (see on this label).
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Wash contaminated clothing before reuse.
IF exposed or concerned: Get medical advice/attention.
If skin irritation or rash occurs: Get medical advice/attention.
If swallowed: Rinse mouth. Do NOT induce vomiting.
In case of fire: Use for extinction: CO₂, powder or water spray.
Collect spillage.
Store locked up.
Store in a well-ventilated place. Keep cool.
Dispose of contents/container in accordance with local/regional/national/international regulations.

• **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

(Contd. on page 12)



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 06/05/2018

Reviewed on 06/05/2018

• State Right to Know		
CAS: 84852-15-3	4-nonylphenol, branched ⚠ Repr. 2, H361; ⚠ Skin Corr. 1B, H314; ⚠ Aquatic Acute 1, H400; ⚠ Aquatic Chronic 1, H410; ⚠ Acute Tox. 4, H302	25-50%
CAS: 1330-20-7 RTECS: ZE 2100000	xylene ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315	15-35%
CAS: 694-83-7	cyclohex-1,2-ylenediamine ⚠ Skin Corr. 1B, H314; ⚠ Eye Dam. 1, H318; ⚠ Skin Sens. 1, H317; H227	5-10%
CAS: 90-72-2	2,4,6-tris(dimethylaminomethyl)phenol ⚠ Acute Tox. 4, H302; ⚠ Skin Irrit. 2, H315; ⚠ Eye Irrit. 2A, H319	5-10%
CAS: 100-51-6 RTECS: DN 3150000	Benzyl alcohol ⚠ Acute Tox. 4, H302; ⚠ Acute Tox. 4, H332	5-10%
All ingredients are listed.		

• **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

• **Date of preparation / last revision 09/22/2017/ 1**

• **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 3: Flammable liquids, Hazard Category 3

: Flammable liquids, Hazard Category 4

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Repr. 2: Reproductive toxicity, Hazard Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - Acute Hazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

• *** Data compared to the previous version altered.**